

TS-1253BU-RP-4G	
Prozessor	Intel Apollo Lake J3455 4-core 1.5GHz
Systemspeicher	4 GB DDR3L (2 x 2 GB)
Speichersteckplatz	SODIMM x 2 (MAX. 8GB)
Flash-Speicher	4GB eMMC
PCIe-Steckplatz	1 x PCIe gen 2 x 2 slot
Laufwerksschacht	12
Laufwerkskompatibilität	SATA 6Gb/s, 3Gb/s HDD or SSD; Hot-swappable
USB-Port	4 x USB 3.0 (Rear)
Gigabit Ethernet Port	4 x GbE
HDMI-Ausgang	1 x HDMI 1.4b
LED-Anzeigen	System Status, HDD, USB, LAN
Tasten	Power, Reset
Systemwarnung	Buzzer
Formfaktor	2U, rack mountable
Abmessungen (H x B x T)	89 x 482 x 534 mm 3.5 x 18.98 x 21.02 inch
Gewicht	Net: 11.64 kg (25.66 lbs) Gross: 15.27 kg (33.66 lbs)
Stromverbrauch (W)	HDD sleep: 42.7W Typical Operation: 75.9W
Geräuschpegel	Operating low speed: 33.2 dB(A)
Betriebstemperatur & relative Luftfeuchtigkeit	0-40°C 0~95% R.H.
Netzteil	ATX 250W
Lüfter	2 x 70mm, 12V DC

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.

\* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.

Designs and specifications are subject to change without notice.